

# Acoustic for Underwater Sensing

## Time and Frequency Modelling

Paulo Santos (pjsantos@ualg.pt)

Centro de Investigação Tecnológica do Algarve (CINTAL)

*Introduction to  
advanced marine technologies*

SUMMER SCHOOL (SS1)  
Almada, Portugal



STRONG  
MAR

29th of June 2016




- Basic concepts of signal processing applied to Underwater acoustics
- The correlation (travel time/ range estimation)
- Linear systems (impulse response and frequency response)
- Time  $\leftrightarrow$  Frequency modelling


# The echosounder<sup>1</sup>

- Object detection
- Range estimation

fathometer (water depth)




fishfinder



<sup>1</sup> pictures from wikipedia

# Principle of range estimation



- 1 A short pulse is transmitted
- 2 The pulse is reflected by the object (reflector)
- 3 The receiver detects the reflected pulse (echo)

- travel time ( $\tau$ ): the period elapsed from the transmission till detection of echo at the receiver
- sound speed in water( $c$ )
- reflector's range

$$r = \frac{c\tau}{2}$$

- $s(t)$  transmitted (pulse) signal,
- $\tau$  travel time (time of flight),
- $a$  attenuation weight, transmission loss and reflection loss,
- $n(t)$  noise,
- $y(t)$  received signal.

$$y(t) = as(t - \tau) + n(t)$$

Questions:


- How to select the signal  $s(t)$  ?
- How to detect the signal?, i.e., How to estimate  $\tau$ ?

# Signal correlation

The **cross-correlation**  $r_{fg}(t)$  between signals  $f(t)$  and  $g(t)$  is a measure of similarity between them as a function of a delay (time-lag),

$$\begin{aligned} r_{fg}(t) &= f(t) \star g(t) \\ &= \int_{-\infty}^{\infty} f(\tau)g(\tau - t)d\tau \\ &= \int_{-\infty}^{\infty} f(t + \tau)g(\tau)d\tau \end{aligned}$$

- $r_{gf}(t) = r_{fg}(-t)$   
(noncommutative)




# Signal autocorrelation

The **Autocorrelation**  $r_{ff}(t)$  is the cross-correlation of a signal with itself.

- $r_{ff}(0)$  represents the energy contents of a signal

$$r_{ff}(0) = \int_{-\infty}^{\infty} |f(\tau)|^2 d\tau$$


- $r_{ff}(t) < r_{ff}(0)$ , when  $t \neq 0$



# Examples of autocorrelation


*chirp*

frequency band 10-20Hz,  
duration 2s



noise sample

white Gaussian  
mean ( $\mu$ ) 0, variance ( $\sigma^2 = 1$ )



- What is the autocorrelation of a sinusoid (ton)?
- Autocorrelation (peak) width is inverse to signal's frequency bandwidth




# Properties(1)

- when  $f(t)$  is  $g(t)$  delayed ( $\tau_0$  is the delay) , i.e  $f(t) = g(t - \tau_0)$ ,

$$r_{fg}(t) = r_{gg}(t - \tau_0)$$

The cross-correlation between  $g(t)$  and  $f(t)$  is the delayed autocorrelation of  $g(t)$ , i.e.  $r_{gg}(t)$  centered at  $\tau_0$



- when  $f(t) = ag(t)$ , where  $a$  is a gain (or attenuation), then


$$r_{fg}(t) = ar_{gg}(t)$$

- the correlation is additive, i.e. the cross-correlation between  $f(t) = u(t) + v(t)$  and  $g(t)$  is equal to the sum of the cross-correlation between  $u(t)$  and  $g(t)$  with the cross-correlation between  $v(t)$  and  $g(t)$

$$r_{gf}(t) = r_{gu}(t) + r_{gv}(t)$$

# Cross-correlation between signal and noise


Chirp's autocorrelation (blue), cross-correlation between chirp and zero mean white Gaussian noise (red)



- Noise is a random signal, therefore we should consider the average correlation over various noise realizations.
- Assuming that signal and noise are independent the average correlation is zero.

# Travel time estimator

- the autocorrelation of the probe (transmitted) signal  $s(t)$  should be narrow (well defined peak)
- perform the cross-correlation between the probe and the received signal  $y(t) = as(t - \tau) + n(t)$




## Travel time estimator

$$\tau = \arg \left\{ \max |r_{ys}(t)|^2 \right\}$$

Once  $\tau$  is estimated, assuming that  $c$  (sound speed) is known, the object range estimation is straightforward.


# Passive localization

- The target transmits broadband signals
- The receivers are synchronized
- The signals received in various receivers are cross-correlated



- $\tau_{ab} = \arg \{ \max |r_{ab}(t)|^2 \}, \dots$
- $\tau_{ab} = \tau_a - \tau_b$   
 $\tau_{ac} = \tau_a - \tau_c$   
 $\tau_{bc} = \tau_b - \tau_c$
- $\tau_{ab}c = r_a - r_b$   
 $\tau_{ac}c = r_a - r_c$   
 $\tau_{bc}c = r_b - r_c$
- solve the linear system to estimate  $r_a, r_b, r_c$

- A system is a transformation (mapping) of inputs into outputs



- Single Input Single Output systems(SISO).


$$y(t) = T[x(t)]$$

- $y(t)$  is the **system response** to system input  $x(t)$

# Linear system (1)

Let  $y(t)$  the response of the system to the input  $x(t)$ :

- Linear systems obey the **principle of superposition** (linearity):
  - Scaled




# Linear system (2)

Let  $y(t)$  the response of the system to the input  $x(t)$ :

- Linear systems obey the **principle of superposition** (linearity):
  - Summed

$$T[x_1(t) + x_2(t)] = T[x_1(t)] + T[x_2(t)]$$



$$x_1(t) \quad \text{-----} \rightarrow y_1(t)$$

$$x_2(t) \quad \text{-----} \rightarrow y_2(t)$$

$$x_3(t)=x_1(t)+x_2(t) \quad \text{-----} \rightarrow y_3(t)=y_1(t)+y_2(t)$$

- Combining both:

$$T[ax_1(t) + bx_2(t)] = aT[x_1(t)] + bT[x_2(t)]$$




# Time invariant system

- A system is **time invariant** if:
  - whether it applies an input to the system now or  $t_0$  seconds later, the output will be identical except for a time delay of  $t_0$


- 

$$y(t) = T[x(t)] \implies y(t - t_0) = T[x(t - t_0)], \forall t_0 \in \mathbb{Z}$$



# Impulse response

- The **impulse response** of a system is its output when the input is an (unit) impulse (dirac function).





- The impulse response characterizes the system.
- For a **linear time-invariant (LTI) system** with impulse response  $h(t)$  and input  $x(t)$ , the output is given by the convolution.

# Convolution & Impulse response

$$y(t) = \int_{-\infty}^{\infty} h(t - \tau)x(\tau)d\tau = \int_{-\infty}^{\infty} h(\tau)x(t - \tau)d\tau = \mathbf{h(t) * x(t)}$$

(convolution (\*) is commutative)




# Frequency response

- The frequency response of a system determines, for a sinusoidal input at a given frequency, the gain and phase shift introduced by the system. For LTI systems:
  - If the input is a sinusoid, the output is also a sinusoid at the same frequency (the amplitude and phase depends on the frequency response)
  - The frequency response  $H(\omega)$  is the Fourier transform of the impulse response  $h(t)$

$$\text{time (t)} \longrightarrow \text{freq. } (\omega) \quad H(\omega) = \mathcal{F}\{h(t)\} = \int_{-\infty}^{+\infty} h(t)e^{-j\omega t} dt$$

$$\text{freq. } (\omega) \longrightarrow \text{time (t)} \quad h(t) = \mathcal{F}^{-1}\{H(\omega)\} = \frac{1}{2\pi} \int_{-\infty}^{+\infty} H(\omega)e^{j\omega t} d\omega$$

# Impulse & Frequency response




$$H(\omega) = Y(\omega) / X(\omega)$$

$$X(\omega), Y(\omega), H(\omega), \quad \mathcal{F}(\text{FT}) \text{ of } x(t), y(t), h(t)$$

# Multipath

- Due to refraction and reflections the waveform transmitted by the source is received as a sum of various echoes.



- Each echo is characterized by the propagation path (trajectory), attenuation and travel time,
  - it depends also on environmental characteristics of the ocean (underwater acoustic channel).

# Impulse response of an underwater channel

- The impulse response is given by:


$$h(t) = \sum_{n=1}^N A_n \delta(t - \tau_n)$$

$N$  number of echoes;  $A_n, \tau_n, n^{th}$  echo attenuation and travel time (delay).

- The received signal  $y(t)$  is given by:

$$y(t) = \sum_{n=1}^N A_n s(t - \tau_n) + n(t)$$

where  $s(t)$  is the transmitted waveform and  $n(t)$  is the noise.



$N, A_n, \tau_n$  characterize the underwater channel between the transmitter and the receiver

# Arrival pattern (1)

How to estimate  $N, A_n, \tau_n$  ?

- Problem of amplitude and time delay estimation of a known signal in noise.
- A possible solution is cross-correlating the received signal  $y(t)$  with the transmitted waveform  $s(t)$ .



## Arrival pattern (2)


- The received signal  $y(t)$  is cross-correlated with transmitted waveform  $s(t)$ :

$$\begin{aligned} E\{y(t) \star s(t)\} &= (\text{using correlation}) \\ E\{y(t) \star s^H(-t)\} &= (\text{using convolution}) \\ E\{[s(t) \star h(t) + n(t)] \star s^H(-t)\} \\ E\{[s(t) \star s^H(-t)] \star h(t)\} + E\{n(t) \star s^H(-t)\} \\ r_{ss} &\approx 0 \end{aligned}$$


$$\begin{aligned} r_{ys}(t) &= r_{ss}(t) \star h(t) \\ &= \sum_{n=1}^N A_n r_{ss}(t - \tau_n), \end{aligned}$$

- the output is a (time) function with  $N$  peaks  $A_1, \dots, A_n$  occurring at delays  $\tau_1, \dots, \tau_N$

# Arrival pattern (3)



Cross-correlation



Arrival pattern

- Arrival pattern

$$a(t) = |r_{ys}(t)|^2.$$



- Very often the amplitudes are represented in decibel (dB-logarithmic scale)

$$r(t) = 10\log(a(t))$$

- Emphasizes latter (weaker) arrivals


# Example: Influence of source location

- OAEx (July 2009), Ilha dos porcos, Arraial do Cabo, Brazil
- sonar source (3-4kHz),
- source range: 50 m to 1200 m,
- 2 hydrophones: 10 m and 20 m depth.







# Example: Surface tide (water depth)

- INTIMATE'98 data set (Gulf of Biscay)
- shallow water (wd 140m, sr 10km)




# Example: physic-chemical parameters ( $O_2$ )

- transmissions over a seagrass bed (*Posidonia oceanica*), Bay of La Revellata, Corsica
- attenuation related to photosynthetic activity (released  $O_2$  bubbles and air in aerenchyma)



# Broadband modeling (time domain modeling)



# Fourier synthesis

- $H(\omega)$  is given by the model
- impulse response

$$h(t) = \int_{-\infty}^{+\infty} H(\omega) e^{j\omega t} d\omega$$

- received signal  $y(t) = s(t) * h(t)$

$$y(t) = \int_{-\infty}^{+\infty} S(\omega) H(\omega) e^{j\omega t} d\omega$$

$S(\omega)$  source's frequency response

- cross-correlation  $r_{ys}(t) = r_{ss}(t) * h(t)$




$$r_{ys}(t) = \int_{-\infty}^{+\infty} S(\omega) S^H(\omega) H(\omega) e^{j\omega t} d\omega$$

# FT of real signals

If  $x(t)$  is a real signal

$$X(-\omega) = X^H(\omega)$$

- the module  $|X(\omega)|$  is an even function
- the argument (phase)  $\angle X(\omega)$  is an odd function
- Model computes  $H(\omega)$  only for positive frequencies





# Practical issues (1)

- select  $f_s$  depending on the max frequency of source signal
- select  $T_0$  depending on the expected time spread of  $h(t)$
- determine  $N$  ( $N \geq \text{round}\{T_0/f_s + 1\}$ )
- determine frequency step  $\Delta f = f_s/N$
- determine the discrete frequencies (frequency indexes) for the signal's band
- determine  $H(\omega)$  (only "positive" frequencies) using a propagation model

# Practical issues (2)

- Normal modes: for the selected frequencies compute  $H(\omega)$
- Ray tracing:
  - compute  $A, \tau$  for the rays set
  - for the central frequency (or selected frequencies) compute  $H(\omega)$  using the time-delay property of FT  $\mathcal{F}\{x(t - t_0)\} = X(\omega)e^{-j\omega t_0}$

$$H(\omega) = \sum_{l=1}^L A_l e^{-j\omega \tau_l}, L \text{ number of rays}$$

- using the FT property of real signals determine the complementary part of  $H(\omega)$
- using inverse DFT (IFFT) compute  $h(t)$ 
  - to compute  $y(t)$  use  $S(\omega)H(\omega)$  (in place of  $H(\omega)$ )
  - to compute  $r_{ys}(t)$  use  $S(\omega)S^H(\omega)H(\omega)$
  - $S(\omega)$  is the source spectrum

# References



Jensen et al., Fundamentals of Computational Acoustics, Springer, 2011



Kuperman W., Roux P., Underwater Acoustics in Springer Handbook of Acoustics, 2007



Etter, P. C., Underwater Acoustic Modeling and Simulation, Spon Press, 2003



Kuperman W. and Lynch J. , Shallow Water Acoustics, Physics Today, American Institute of Physics, October 2004.



Hansen R., Introduction to Sonar, Course material to INF-GEO4310, University of Oslo, 2011.

*Thank you for your attention!*



**STRONG  
MAR**

*[www.strongmar.eu](http://www.strongmar.eu)*

**Paulo Santos**  
**[pjsantos@ualg.pt](mailto:pjsantos@ualg.pt)**

The STRONGMAR project is funded by the European Commission under the H2020 EU Framework Programme for Research and Innovation (H2020-TWINN-2015, 692427).

